

PRODUCT DATASHEET

NOLA100_60W_LED_6000

Dust and water resistant LED luminaire, IP65, IK08,

Electronic, fixed output control gear.

Housing: white Polycarbonate (PC). Diffuser:

Polycarbonate (PC) . For surface or suspended mounting

Supplied with quick-fix brackets, for surface

mounting. Complete with 4000K LED.



IP65

IK08

102,16 lm/W

TECHNICAL DATA

SKU:

6007000021

Electrical data

Nominal wattage	60 W
Operating wattage	58.73 W
Nominal Voltage	165-240 V
Power factor	≥0.90
Mains frequency	50/60 Hz

Photometrical data

Color temperature (CCT)	4000 K
Luminous efficiency	102,16 lm/W
Luminous flux	6000 lm
Color rendering index (CRI)	≥80
Unified Glare Rating (UGR)	<21,5

Light technical data

Beam angle	120°
------------	------

Dimensions and weight

Dimension	1230×80x45 mm
Weight Neto	0,494 kg

Materials

Body material	Polycarbonate (PC)
Housing color	White
Difuser material	Polycarbonate (PC)

Operating conditions

Ambient temperature range	-20...+65°C
---------------------------	-------------

Lifespan

Lifespan L80/B10 at 25°	50000 h
Led Brand	EPISTAR
Driver	Integrated

Mounting information

Mounting type	Surfaced / Suspended
Mounting location	Ceiling / Wall
Capabilities	
Dimmable	No
Type of connection	Via 2 fixing holes
Standards and Certificates	
Protection class IK	IK08
Type of protection IP	IP65
Standards	CE, RoHS
Warranty	36 months

LOGISTICAL DATA

Main package


Product code	6007000021
Package	Paper and plastic
Units in carton	1 pcs
Package diameters, weight bruto	1230x85x50 mm, 0,550 kg
Product EAN code	4772007011087

Second package

Package	Carton box
Units in second package	10 pcs
Package diameters, weight bruto	1260x280x190 mm ; 6,426 kg
ShipPing carton EAN code	4772007011094

ACCESSORIES

ENERGY EFFICIENCY



ALL FAMILY PRODUCTS

6007000019	NOLA100_30W_LED_3000
6007000020	NOLA100_36W_LED_3600
6007000021	NOLA100_60W_LED_6000
6007000022	NOLA100_70W_LED_7000