



FWB32

**FWB encl. univers,3rows 72 mod cl.II IP44,plain door,500x550x161mm,brass term.**

**Technical properties**

**Architecture**

Fixing mode surface-mounting

**Functions**

With a pipe-in lead Yes

Protection main switch No

**Configuration**

Module with terminals

Number of modules 72

**Compatibility**

Suitable for Multimedia No

**Electric current**

Rated current 125 A

**Dimensions**

Insertion depth 161 mm

Depth of installed product 165 mm

Internal depth 156 mm

Height of installed product 500 mm

Installation height 500 mm

Width of installed product 550 mm

Width in division units 24

Thickness of sidewall material 1 mm

**Cover, door**

Type of door closing hinged pattern handle

Number of keylock of the door 1

Cover type With Notch

Door locking without

Door leave single

Cover type Door

Transparent cover or door No

**Materials**

Colour white

Colour white

RAL colour RAL 9010 - Pure white

Material	Steel
Type of surface treatment	powder-coated
<b>Installation, mounting</b>	
Suitable for outdoor use	No
<b>Connection</b>	
Number of conduit inlets	8
<b>Settings</b>	
Enclosure type	Field distributor surface mounted
<b>Equipment</b>	
Number of rows	6
Quantity of section in width	2
Number of keys	1
Can be accessorized	Yes
Number of openings for flange plates	4
Extension possible	Yes
Earthing terminal block	No
Neutral terminal block	Yes
Signal passing door	No
<b>Standards</b>	
GWT Glow wire test	750 °C
European directive WEEE	concerned
<b>Safety</b>	
IK protection code against mechanical impacts	IK09
Protection index IP	IP44
Protection class	isol.class II
Halogen free	No
<b>Identification</b>	
meta_keyword	Unifers;metal field distributor;surface-mounted;protection class II;